


E-ZWELD®

**New & Improved Specially for
Kingdom of Saudi Arabia**

World's First CPVC Cement with 3 year shelf life !



- Orange, Low-Voc Heavy Body, medium set CPVC cement for use on all classes and schedules of CPVC pipe and fittings with interference fit up to 12" (315 mm) diameter.
- Our best CPVC cement that has excellent gap filling properties.
- Formulated for total compatibility with **FLOWGUARD GOLD®** systems, that is a Registered trademark of Lubrizol Company.
- Recommended for residential and commercial hot and cold water systems up to 180°F (82°C).
- Recommended application temperature 32°F to 110°F / 0°C to 43°C.
- Meets ASTM F-493 and ASTM D-2846.
- 3 Year Shelf Life - Unopened Can.
- Can Sizes : 4 oz / 118 ml, 8 oz / 237 ml, 16 oz / 473 ml, 32 oz / 946 ml
2 oz / 59 ml can, 2 oz 59 ml tube (Made to Order)



E-Z WELD (U.S.A. Headquarters)
1661 Old Dixie Hwy,
Riviera Beach, Florida 33404
+1-800-327-8460
+1-561-844-0241
Fax: +1-561-848-8958

E-Z WELD (Branch)
Business Centre, Dubai World Central
P.O. Box 390667
Dubai, United Arab Emirates
Phone: +97156 4468564
email: sdadlani@e-zweld.com






MADE IN USA




WWW.E-ZWELD.COM




E-ZWELD


E-ZWELD®




CPVC / PVC / uPVC Solvent Cements, Cleaners & Primers

	786 CPVC CEMENT HEAVY BODY/ORANGE	Industry Listing	Hydrostatic Burst Strength	Size	Part Number
	<ul style="list-style-type: none"> Orange, Low-Voc Heavy Body, medium set CPVC cement for use on all classes and schedules of CPVC pipe and fittings with interference fit up to 315) "12 mm) diameter Our best CPVC cement that has excellent gap filling properties Formulated for total compatibility with Flow Guard Gold® systems. Flowguard Gold is Registered trademark of Lubrizol Corp. Recommended for residential and commercial hot and cold water systems up to 180°F (82°C) Recommended application temperature 32°F to 110°F / 0°C to 43°C Meets ASTM F-493 and ASTM D-2846 	 	Minimum 400 psi after 2 hour cure @ 73°F	4 oz / 118 ml 8 oz / 237 ml 16 oz / 473 ml 32 oz / 946 ml	78601 78602 78603 78604
				Made to Order 2 oz / 59 ml Can 2 oz / 59 ml Tube	78606 78600

	766 PVC/uPVC CEMENT REG. BODY/CLEAR	Industry Listing	Hydrostatic Burst Strength	Lap Shear Strength	Size	Part Number
	<ul style="list-style-type: none"> Clear, Low-VOC Regular Body, fast set PVC/uPVC cement for use on PVC/uPVC pipe and fittings up to 110) "4 mm) for DWV Sch. 40 and up to 2" (55 mm) for Sch. 80. Can be used for potable water, pressure / non pressure applications, conduit and DWV Recommended application temperature 32°F to 110°F / 0°C to 43°C Meets ASTM D-2564 	 	Minimum 400 psi after 2 hour cure @ 73°F	Minimum 250 psi after 2 hour cure @ 73°F	4 oz / 118 ml 8 oz / 237 ml 16 oz / 473 ml 32 oz / 946 ml 128 oz / 3.8 L	76601 76602 76603 76604 76605

	755 PVC/uPVC CEMENT HEAVY BODY/GRAY	Industry Listing	Hydrostatic Burst Strength	Lap Shear Strength	Size	Part Number
	<ul style="list-style-type: none"> Gray, Low-VOC Heavy Body, medium set PVC/uPVC cement (gray version of EZ-Weld 218 Clear) for use on all classes & schedules of PVC/uPVC pipe and fittings with interference fit through 475) "18 mm) diameter A high quality cement specially formulated for gap fill, recommended for potable water, pressure / non pressure applications, conduit and DWV Recommended application temperature 32°F to 110°F / 0°C to 43°C Meets ASTM D-2564 	 	Minimum 400 psi after 2 hour cure @ 73°F	Minimum 250 psi after 2 hour cure @ 73°F	4 oz / 118 ml 8 oz / 237 ml 16 oz / 473 ml 32 oz / 946 ml 128 oz / 3.8 L	75501 75502 75503 75504 75505

	733 PIPE CLEANER				Size	Part Number
	<ul style="list-style-type: none"> Clear, Low-VOC fast acting cleaner effectively removes oil and grease from surfaces of all schedules and sizes of PVC/uPVC, CPVC, ABS, and STYRENE pipe and fittings Highly recommended for use before priming of pipe and fittings 				4 oz / 118 ml 8 oz / 237 ml 16 oz / 473 ml 32 oz / 946 ml 128 oz / 3.8 L	73301 73302 73303 73304 73305

	722 PURPLE PRIMER			Industry Listing	Size	Part Number
	<ul style="list-style-type: none"> Purple, Low-VOC fast acting primer for proper softening and preparation of all schedules and sizes of PVC/uPVC and CPVC pipe and fitting surfaces For use in areas where plumbing code calls for verification that a primer must be used Meets ASTM F-656 			 	4 oz / 118 ml 8 oz / 237 ml 16 oz / 473 ml 32 oz / 946 ml 128 oz / 3.8 L	72201 72202 72203 72204 72205
CAUTION: Do not use on ABS or thin walled PVC/uPVC pipes and fittings						

Mahill Trading Corp.  مؤسسة الماهل التجارية

Authorized Importer & Distributor

of E-Z Weld Branded Solvent Cements, Cleaners & Primers in the Kingdom of Saudi Arabia

Riyadh
 T : (011) 244 7414
 F : (011) 244 7449
 E : riyadh@mahill.sa

Jeddah
 T : (012) 227 6140
 F : (012) 227 6144
 E : jeddah@mahill.sa

Dammam
 T : (013) 834 0960
 F : (013) 833 2903
 E : dammam@mahill.sa

WWW.MAHILL.SA